



WEVER & DUCRÉ
LIGHTING

ODREY on track 1.3 LED

187365BB3

| |
|----------|
| Project |
| Type |
| Notes |
| Quantity |
| Date |

GENERAL

Ceiling
 Track
 Jet Black
 IP20
 Interior
 485 lm

LED



2700 K

PHYSICAL

Diameter 100 mm
 Height 170 mm
 0.27 kg
 48V System

ELECTRICAL

DALI dim
 48 V
 Total connected power 8 W
 LED Inset 8 W
 PC3
 Safety distance 0.3 m





WEVER & DUCRÉ
LIGHTING

ODREY on track 1.3 LED

187365BB3

ELECTRICAL

Track Profile 2m

| TYPE | COLOUR | L - W - H (MM) | ORDERCODE |
|--|--------|-----------------|---------------------|
| STREX system custom cut suspended indirect light | Black | 1000-1999-26-29 | 9 0 0 1 4 0 B 5 C C |
| STREX system custom cut suspended indirect light | White | 1000-1999-26-29 | 9 0 0 1 4 0 W 5 C C |
| STREX system custom cut surface/suspended | White | 1001-1999-26-29 | 9 0 0 1 4 1 8 3 C C |
| STREX system custom cut surface/suspended | Black | 1001-1999-26-29 | 9 0 0 1 4 1 8 4 C C |
| STREX system custom cut recessed | White | 1001-1999-37-33 | 9 0 0 1 4 1 8 9 C C |
| STREX system custom cut recessed | Black | 1001-1999-37-33 | 9 0 0 1 4 1 9 0 C C |
| STREX system suspended indirect light | Black | 2000-26-29 | 9 0 0 1 4 0 B 5 |
| STREX system suspended indirect light | White | 2000-26-29 | 9 0 0 1 4 0 W 5 |
| STREX system surface/suspended | White | 2000-26-29 | 9 0 0 1 4 1 8 3 |
| STREX system surface/suspended | Black | 2000-26-29 | 9 0 0 1 4 1 8 4 |
| STREX system recessed | White | 2000-37-33 | 9 0 0 1 4 1 8 9 |
| STREX system recessed | Black | 2000-37-33 | 9 0 0 1 4 1 9 0 |

Track Profile 1m

| TYPE | COLOUR | L - W - H (MM) | ORDERCODE |
|---|--------|----------------|---------------------|
| STREX system custom cut surface/suspended | White | 200-999-26-29 | 9 0 0 1 4 1 8 1 C C |
| STREX system custom cut surface/suspended | Black | 200-999-26-29 | 9 0 0 1 4 1 8 2 C C |
| STREX system custom cut recessed | White | 200-999-37-33 | 9 0 0 1 4 1 8 7 C C |
| STREX system custom cut recessed | Black | 200-999-37-33 | 9 0 0 1 4 1 8 8 C C |
| STREX system surface/suspended | White | 1000-26-29 | 9 0 0 1 4 1 8 1 |
| STREX system surface/suspended | Black | 1000-26-29 | 9 0 0 1 4 1 8 2 |
| STREX system recessed | White | 1000-37-33 | 9 0 0 1 4 1 8 7 |
| STREX system recessed | Black | 1000-37-33 | 9 0 0 1 4 1 8 8 |

Track Profile 3m

| TYPE | COLOUR | L - W - H (MM) | ORDERCODE |
|--|--------|-----------------|---------------------|
| STREX system custom cut surface/suspended | White | 2001-2999-26-29 | 9 0 0 1 4 1 8 5 C C |
| STREX system custom cut surface/suspended | Black | 2001-2999-26-29 | 9 0 0 1 4 1 8 6 C C |
| STREX system custom cut recessed | White | 2001-2999-37-33 | 9 0 0 1 4 1 9 1 C C |
| STREX system custom cut recessed | Black | 2001-2999-37-33 | 9 0 0 1 4 1 9 2 C C |
| STREX system custom cut suspended indirect light | Black | 2001-2999-26-29 | 9 0 0 1 4 1 B 5 C C |
| STREX system custom cut suspended indirect light | White | 2001-2999-26-29 | 9 0 0 1 4 1 W 5 C C |
| STREX system surface/suspended | White | 3000-26-29 | 9 0 0 1 4 1 8 5 |
| STREX system surface/suspended | Black | 3000-26-29 | 9 0 0 1 4 1 8 6 |
| STREX system recessed | White | 3000-37-33 | 9 0 0 1 4 1 9 1 |
| STREX system recessed | Black | 3000-37-33 | 9 0 0 1 4 1 9 2 |
| STREX system suspended indirect light | Black | 3000-26-29 | 9 0 0 1 4 1 B 5 |
| STREX system suspended indirect light | White | 3000-26-29 | 9 0 0 1 4 1 W 5 |

[187365BB3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

ODREY on track 1.3 LED

187365BB3

In Track Driver 100W

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------------------|--------|----------------|-----------------|
| STREX system surface | Black | 438-16-18 | 9 0 0 1 4 1 4 3 |
| STREX system surface | White | 438-16-18 | 9 0 0 1 4 1 4 4 |
| STREX system suspended | White | 3000 | 9 0 0 1 4 1 5 7 |
| STREX system suspended | Black | 3000 | 9 0 0 1 4 1 7 4 |
| STREX system surface | Black | 468-26-29 | 9 0 0 1 4 1 7 6 |
| STREX system surface | White | 468-26-29 | 9 0 0 1 4 1 7 8 |

In Track Driver 250W

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------------------|--------|----------------|-----------------|
| STREX system surface | Black | 408-16-18 | 9 0 0 1 4 1 4 5 |
| STREX system surface | White | 408-16-18 | 9 0 0 1 4 1 4 6 |
| STREX system suspended | White | 3000 | 9 0 0 1 4 1 5 8 |
| STREX system suspended | Black | 3000 | 9 0 0 1 4 1 7 5 |
| STREX system surface | Black | 438-26-29 | 9 0 0 1 4 1 7 7 |
| STREX system surface | White | 438-26-29 | 9 0 0 1 4 1 7 9 |

End Cap

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|----------------------------------|--------|----------------|-----------------|
| STREX system surface/suspended | White | 26-2.5-29 | 9 0 0 1 4 1 4 7 |
| STREX system surface/suspended | Black | 26-2.5-29 | 9 0 0 1 4 1 4 8 |
| STREX system recessed | White | 37-10-27 | 9 0 0 1 4 1 4 9 |
| STREX system recessed | Black | 37-10-27 | 9 0 0 1 4 1 5 0 |

Power Feed

| TYPE | COLOUR | L · H (MM) | ORDERCODE |
|--------------|--------|------------|-----------------|
| STREX system | White | 112-18 | 9 0 0 1 4 1 5 3 |
| STREX system | Black | 112-18 | 9 0 0 1 4 1 5 4 |

Wireless Casambi Control

| TYPE | COLOUR | L · H (MM) | ORDERCODE |
|--------------|--------|------------|-----------------|
| STREX system | White | 143-58 | 9 0 0 1 4 1 5 5 |
| STREX system | Black | 143-58 | 9 0 0 1 4 1 5 6 |

Suspension Set

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|---------------------------------|-----------------|----------------|-----------------|
| STREX system 1.5m suspended | Stainless Steel | 80-23-1500 | 9 0 0 1 4 1 6 0 |
| STREX system 3.0m suspended | Stainless Steel | 80-23-3000 | 9 0 0 1 4 1 6 1 |
| STREX system 1.5m suspended | Black | 80-23-1500 | 9 0 0 1 4 2 7 4 |
| STREX system 3.0m suspended | Black | 80-23-3000 | 9 0 0 1 4 2 7 5 |

Power Supply 100W

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------------------|--------|----------------|-----------------|
| STREX system surface | White | 439-26-44 | 9 0 0 1 4 1 6 6 |
| STREX system surface | Black | 439-26-44 | 9 0 0 1 4 1 6 7 |
| STREX system suspended | White | 439-26-44 | 9 0 0 1 4 1 6 8 |
| STREX system suspended | Black | 439-26-44 | 9 0 0 1 4 1 6 9 |
| STREX system suspended | White | 439-26-44 | 9 0 0 1 4 2 6 0 |
| STREX system suspended | Black | 439-26-44 | 9 0 0 1 4 2 6 1 |
| STREX system | | 350-30-18 | 9 0 2 1 8 9 0 1 |

[187365BB3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

ODREY on track 1.3 LED

187365BB3

Power Supply 150W

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------------------|--------|----------------|-----------------|
| STREX system surface | White | 439·26·44 | 9 0 0 1 4 1 7 0 |
| STREX system surface | Black | 439·26·44 | 9 0 0 1 4 1 7 1 |
| STREX system suspended | White | 439·26·44 | 9 0 0 1 4 1 7 2 |
| STREX system suspended | Black | 439·26·44 | 9 0 0 1 4 1 7 3 |
| STREX system suspended | White | 439·26·44 | 9 0 0 1 4 2 6 2 |
| STREX system suspended | Black | 439·26·44 | 9 0 0 1 4 2 6 3 |
| STREX system | | 350·30·18 | 9 0 2 1 8 9 0 2 |

Mounting Bracket

| TYPE | ORDERCODE |
|-------------------------|-----------------|
| STREX system recessed | 9 0 0 1 4 1 9 3 |

Connector

| TYPE | COLOUR | L · H (MM) | ORDERCODE |
|--------------|--------|------------|-----------------|
| STREX system | White | 105·18 | 9 0 0 1 4 1 9 6 |
| STREX system | Black | 105·18 | 9 0 0 1 4 1 9 7 |

L-Connector

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|----------------------------------|--------|----------------|-----------------|
| STREX system surface/suspended | White | 105·105·18 | 9 0 0 1 4 1 9 8 |
| STREX system surface/suspended | Black | 105·105·18 | 9 0 0 1 4 1 9 9 |
| STREX system recessed | White | 105·105·18 | 9 0 0 1 4 2 5 1 |
| STREX system recessed | Black | 105·105·18 | 9 0 0 1 4 2 5 2 |

L-Connector non-electrical

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|-------------------------|--------|----------------|-----------------|
| STREX system recessed | White | 105·105·18 | 9 0 0 1 4 2 5 6 |
| STREX system recessed | Black | 105·105·18 | 9 0 0 1 4 2 5 7 |
| STREX system surface | White | 105·105·18 | 9 0 0 1 4 2 5 8 |
| STREX system surface | Black | 105·105·18 | 9 0 0 1 4 2 5 9 |

DALI Selv Device

| TYPE | L · W · H (MM) | ORDERCODE |
|--------------|----------------|-----------------|
| STREX system | 213·37·25 | 9 0 0 1 9 1 9 3 |



37

213

215

Power Supply 250W

| TYPE | L · W · H (MM) | ORDERCODE |
|--------------|----------------|-----------------|
| STREX system | 400·40·22 | 9 0 2 1 8 9 0 3 |

Blank Cover 1m

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------|--------|----------------|-----------------|
| STREX system | Black | 1000·18·3 | 9 1 1 0 0 1 B 0 |
| STREX system | White | 1000·18·3 | 9 1 1 0 0 1 W 0 |

[187365BB3] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BV apply.
© Wever & Ducré BV · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

ODREY

on track 1.3 LED

187365BB3

Blank Cover 2m

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------|--------|----------------|-----------------|
| STREX system | Black | 2000·18·3 | 9 1 1 0 0 2 B 0 |
| STREX system | White | 2000·18·3 | 9 1 1 0 0 2 W 0 |

Blank Cover 3m

| TYPE | COLOUR | L · W · H (MM) | ORDERCODE |
|--------------|--------|----------------|-----------------|
| STREX system | Black | 3000·18·3 | 9 1 1 0 0 3 B 0 |
| STREX system | White | 3000·18·3 | 9 1 1 0 0 3 W 0 |