



F0273000 Black

Noctambule Suspension 2 Low Cylinder Bowl

Designed by Konstantin Grcic, 2019




45W - 1007lm - 2700K - CRI> 90

Hanging lamps consisting of interconnecting glass modules reaching a length of 3,2 mt. (126.77") with 4 mt. (157.48") suspended power cable. Cylindrical and semispherical transparent blown glass structure, suspended die cast aluminium ring connector, hydroformed steel internal lateral arm and injection moulded optical opal silicone outer ring diffusers. The power supply unit within the ceiling rose can be used as a dimmer to adjust the light intensity by 10% to 100% in either direction by means of the 0-10/1-10V, PUSH, DALI control.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607000687		
Mounting	Suspension		
Environments	Indoor dry location		
Light Source Type	LED		
LED type	LED Module		
Power (W)	45		
System flux (lm)	1007		

Physical

Colour	Black
Length (mm)	250
Cord length (mm)	4000
Canopy dimension (mm)	45
Canopy width (mm)	187
Net weight (kg)	14.2
Package height (mm)	0
Package width (mm)	0
Package length (mm)	0
Package volume (m3)	0.5
IP internal	20

Download	
Mounting instructions	业 PDF
Mounting instructions	业 PDF
Spare Parts	业 PDF
Photometric Files LDT/IES	⊥ ZIP
Technical Drawings	
3D	<u>↓</u> ZIP
a Bim	↓ ZIP

https://professional.flos.com/en/global/product/noctambule-suspension-2-low-cylinder-bowl-f0273000/

F0273000

















Ecodesign and Energy

This product contains a light

source of energy efficiency

Replaceable (LED only)

light source by a professional

Replaceable control gear by a professional


Labelling

class E





Schematic light drawing



Electrical

Insulation class	1
Frequency (Hz)	50/60
Main voltage (Vac)	120-277
LED voltage Vf (Vdc)	null
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable Push, Dimmable 1-10V, Dimmable DALI 1
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Photometric

Lighting type	Total
Light distribution	Symmetric
CCT (K)	2700
CRI>	90



01.	Power supply kit for	RF0410500
	Arrangements small &	
	Noctambule	
02.	Led dimmer kit	RF0410300
03.	Noctambule ceiling rose cover	RF27422
04.	Suspension attack	F0253030
05.	Ring led diffuser	RF27498
06.	Fixing screws kit	RF0254100
07.	Noctambule Low Cylinder	F0254000
10.	Noctambule Bowl	F0255000

DOWNLOAD









RF0410500

Power supply kit for Arrangements small & Noctambule

Led dimmer kit

RF27422

Noctambule ceiling rose cover

Suspension attack











Ring led diffuser

Fixing screws kit

Noctambule Low Cylinder

Noctambule Bowl