



Mayday Outdoor


Designed by Konstantin Grcic, 2000



Socket for E14 bulb, light source not included. 220-240 V ON/OFF electric power supply. IP65 switch on the handle of the luminaire. It has a 6 meter long cable for outdoor use and an IP44 Schuko plug.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT







Main specifications

Mounting	Hand lamp
Environments	Outdoor wet location
Lamp category	LED retrofit
Lamp holders	E14
Number of heads	1
Power (W)	max 10

IΡ

65

Physical

Colour	Black
Orientation	Fixed
Net weight (kg)	0.9
IP internal	65

Download

Mounting instructions

<u>↓</u> ZIP

Photometric Files

 LDT / IES
 ₺ ZIP


 LDT / IES
 ₺ ZIP

Technical Drawings

2D	<u>↓</u> ZIP
3D	⊥ ZIP

Schematic light drawing

ΙK



Luminous flux **l**uminaire 931 lm

Photometric

Lighting type


Direct


Electrical

Insulation class	II
Frequency (Hz)	50-60
Main voltage (Vac)	220-240
Dimmable	No
Emergency type	No

Notes

Bulb not included. LED: max 10W - E14





NOT INCLUDED

LED Lamp E14 8W 2700K T28

NOT INCLUDED

LED Lamp E14 8W 3000K T28